



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® POWER POINT® 230 Advanced Elastomeric Acrylic Latex Sealant

PRODUCT DESCRIPTION

DAP® POWER POINT® 230 ADVANCED ELASTOMERIC ACRYLIC LATEX SEALANT is specifically formulated for demanding interior and exterior applications, especially molding & trim applications. It delivers excellent adhesion & flexibility for a crack proof seal. It is easy to apply and tool in any climate and is paintable in just 30 minutes. It provides a durable, long lasting seal that will not shine through or discolor paint. Waterproof & weatherproof. Cured sealant is mold & mildew resistant. 60 Year. Exceeds ASTM Specification C920, Class 12.5. Interior/exterior use.



PACKAGING	COLOR	UPC
10.1 fl oz (300 mL) Cartridge	White	7079818800

KEY FEATURES & BENEFITS

- Ideal for wood, PVC & composite molding & trim
- 60 Year
- Paintable in 30 minutes
- Tools in all climates
- Outstanding adhesion & flexibility for a crackproof seal
- 100% waterproof & weatherproof
- Easy water clean-up & low odor
- Cured sealant is mold & mildew resistant
- Exceeds ASTM C920, Class 12.5
- VOC compliant
- Interior/exterior use



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

USE FOR CAULKING & SEALING:

- Windows
- Doors
- Siding
- Trim
- Molding
- Pipes
- Vents
- Corner Joints
- Butt Joints
- Tuck Pointing
- Other gaps & cracks, especially prior to painting

ADHERES TO:

- Wood – painted & unpainted
- Aluminum
- Most metals
- Vinyl
- Most plastics
- Plaster
- Drywall
- Glass
- Fiber Cement
- Stucco
- Composite
- PVC trimboard
- Brick
- Stone
- Concrete
- Mortar
- Most common building materials

FOR BEST RESULTS

- Apply in temperatures above 40°F.
- Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.
- Not for continuous underwater use or filling surface defects.
- Joint size should not exceed 1/2" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material.
- Store sealant away from extreme heat or cold.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all old caulk, dirt and other foreign material.

Product Application

1. Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

2. Cut nozzle at 45° angle to desired bead size.
3. Load cartridge into caulk gun.
4. Fill gap or joint with sealant.
5. If necessary, tool or smooth the bead of sealant with a finishing tool before sealant skins over.
6. Clean up excess wet sealant with a damp sponge before it skins over. Excess dried sealant must be cut or scraped away.
7. Allow sealant to dry 30 minutes (longer in cool or humid conditions) before painting with latex or oil-based paints.
8. Reseal cartridge for storage and reuse.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Gunnable, non-sag paste
Base Polymer	Advanced acrylic polymer
Filler	Calcium carbonate
Volatile	Water
Weight % Solids	80%
Density (lbs per gallon)	12.7
Odor	Very mild
Clean Up	Water
Flash Point	>212°F
Freeze Thaw Stability (ASTM C1183)	Passes 5 cycles
Shelf Life	12 months
Coverage	10.1 fl oz cartridge: 55 linear ft. at a 3/16" bead size
Typical Application Properties	
Application Temperature Range	40°F to 100°F
Tooling Time (Working Time)	10 minutes
Tack Free Time	15 minutes
Full Dry Through	24 hours
Return to Service Time	24 hours
Vertical Sag (ASTM D2202)	0.05"
Typical Cured Performance Properties	
Service Temperature Range	-30°F to 180°F
Water Ready Time	24 hours



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Paint Ready Time	30 minutes
Mildew Resistance	Cured caulk is mold & mildew resistant
Dynamic Joint Movement (ASTM C719)	+/- 12.5%

CLEAN UP & STORAGE

Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS sheet by visiting our website at dap.com or calling 888-DAP-TIPS.

WARRANTY

WARRANTY: If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com