



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Ceiling Spray Texture: Popcorn Water Based

PRODUCT DESCRIPTION



DAP® Ceiling Spray Texture Popcorn Water Based is an easy-to-use aerosol that provides excellent texture match. Its white, sag-resistant formula has strong ceiling adhesion and does not require painting or priming. Fast dry time of 30 minutes, depending on temperature, humidity & amount applied. Interior/Exterior.

PACKAGING	COLOR	UPC
16 oz can	White	7079850035

KEY FEATURES & BENEFITS

- Ideal for ceiling applications
- Excellent match to textured surfaces
- 30-minute paint ready time depending on temperature, humidity & amount applied
- Sag-resistant formula
- No priming required
- Low odor
- Easy water clean-up
- Interior/ Exterior

SUGGESTED USES

USE FOR REPAIRING TEXTURED SURFACES

- Drywall
- Stucco
- Plaster



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- **IMPORTANT:** Shake well before and frequently during spraying
- Cover surrounding areas to protect from over spray
- Apply in temperatures above 40°F
- Dispense a quick burst on scrap material to activate pressure
- Practice applying on scrap material before applying
- Spray using intermittent bursts
- Store away from direct heat in temperatures ranging from 40°F to 90°F
- While this formula does not require priming prior to paint application, priming may still be desired depending on your project/application requirements.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound, and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.

Product Application

1. **SHAKE** can upside down vigorously for more than a minute after hearing mixing marble moving freely in the can. Remove over-cap.
2. **INSERT STRAW** attachment into tip of actuator.
IMPORTANT: Dispense a quick burst of material on scrap materials to activate pressure before applying to surface.
3. **SPRAY** by placing finger on designated indentation at the base of the actuator, holding can approximately 12 inches away from ceiling. **DO NOT SPRAY** directly above you. Spray using intermittent bursts. For optimal blending, use different stroke motions or a circular pattern. Apply texture in overlapping passes to avoid gaps or uneven spots. If not satisfied, scrape-off and reapply. **IMPORTANT:** Be sure that the area is well ventilated and proper safety gear is worn.
4. **PAINT:** Allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow the paint manufacturer's instructions for best results. For exterior applications, use exterior grade paint.
5. **CLEAN-UP** straw, nozzle, tools, and area with towel and warm water. Invert can pointing the top straight down. Spray a quick burst onto a trash can until texture is cleared from outlet. Remove any texture build-up from the actuator tip.
6. **STORE** at room temperature, avoid extreme cold or heat.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	46
Density (lbs per gallon)	10.4
Odor	Low Odor
Clean Up	Water
Shelf Life	12 months
Calculated Coverage	Up to 9 sq. ft. depending on thickness of application
Typical Application Properties	
Application Temperature Range	Best between 60°F to 85°F

CLEAN UP & STORAGE

Clean up excess wet spray texture with warm water and soap. Excess dried spray texture must be cut or scraped away. Clean skin with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

LIMITED WARRANTY

Limited Warranty: If product fails to perform as directed within one year from the date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland

21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com