



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Weatherproof Patching Compound

PRODUCT DESCRIPTION

DAP® Weatherproof Patching Compound is a ready-to-use formula with WeatherMax Technology providing a weather & waterproof repair that is mold, mildew and algae resistant. Allows you to repair holes, cracks, breaks or gaps on a variety of materials including most uncoated metals, composite, PVC, fiber cement, wood and more. It is a durable solution that offers superior strength and adhesion that exterior repairs demand. Easy to use and sandable/paintable. Interior/Exterior use.



PACKAGING	COLOR	UPC
16 fl oz tub	White	7079818741
32 fl oz tub	White	7079818787

KEY FEATURES & BENEFITS

- Horizontal, vertical & overhead applications of a variety of surfaces
- WeatherMax Technology: weather/waterproof, mold, mildew & algae resistant
- Sandable/paintable
- 2-4 hours paint ready
- 24-hour rain ready
- Interior/exterior applications

SUGGESTED USES

USE FOR REPAIRING HOLES, CRACKS, BREAKS, DENTS:

- PVC piping
- Aluminum Steel
- Composite
- Fiber Cement
- Wood
- Concrete
- Vinyl
- Stucco
- Plaster
- Drywall
- Masonry or bricks



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- Do not apply when temperatures are below 40°F.
- Allow product to fully cure before exposing to water, approximately 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- A topcoat is not required, however, if desired, product can be painted with a high-quality latex-based paint.
- Staining is not recommended.
- Not for continuous underwater use.

APPLICATION

Surface Preparation

Surface must be clean, structurally sound, and free of all foreign material.

Product Application

1. Apply in temperatures above 40°F. Do not apply when freezing temperatures are forecasted within 24 hours.
2. Apply with a clean putty knife.
3. For a smoother finish, dip putty knife in water and lightly smooth.
4. One application is usually sufficient for small repairs. For repairs deeper than 1/8", apply two or more layers allowing to dry in between applications.
5. May be sanded and/or painted in 2 to 4 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
6. Clean tools immediately with water.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties (Mixed)	
Appearance/Consistency	Paste
Color	White
Base Polymer	Acrylic Latex
Volatile	Water
Flash Point	212 °F
Filler	Inert Filler
Odor	Mild
Weight/Gallon	13 lbs./gallon
Solids	79%
Clean Up	Water
Freeze Thaw Stability (ASTM C1183)	5 cycles at 0°F/ 8 hours at 73°F
Shelf Life	12 months
Typical Application Properties	
Application Temperature Range	40°F to 120 °F
Cure Time	2 to 4 hours depending on temperature, humidity & depth of fill.
Service Temperature	0°F to 120°F
Typical Cured Performance Properties	
Rain Ready Time	24 hours
Mildew Resistance	Cured is mold & mildew resistant

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried product must be cut or scraped away. Be sure container is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS sheet by calling 888-DAP-TIPS or visiting our website at dap.com.

07/01/2024



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

LIMITED WARRANTY: If product fails to perform when used as directed within one year of date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com