



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Ready-To-Use Concrete Patch

PRODUCT DESCRIPTION

DAP® Ready-To-Use Concrete Patch is a ready to use latex-based compound with fiber reinforcement to increase durability & for a long-lasting repair. Perfect for repairing holes, cracks, breaks & spalls in concrete or masonry surfaces. The textured material is easy to trowel and smooth for a seamless finish. Provides outstanding adhesion to concrete both aged and green. The product is excellent for tuck pointing masonry and brick work. It may also be used as a “glue” to join broken pieces of concrete or brick. **DO NOT USE AS A SKIM COAT.** The material dries to a concrete-gray color. Interior/Exterior.



PACKAGING	COLOR	UPC
Quart	Gray	7079831082, 7079831084
Gallon	Gray	7079831090

KEY FEATURES & BENEFITS

- Repairs cracks and breaks in concrete and masonry
- Durable and shrink-resistant
- Can be used to spot level

SUGGESTED USES

Ideal for filling holes, cracks, dents and other small defects on concrete and masonry surfaces.

APPLICATION

1. Use a wire brush, chisel, or similar tool to remove all loose material, dust, dirt, oil and grease from the area to be repaired. Use a solvent to remove oil and grease. Rough up the surface one or two inches beyond the area to be repaired for a good bond. Dampen the area with clean water – **DO NOT FLOOD.**
2. Stir the patch to a smooth consistency; no thinning is required. With a flexible putty knife, broad knife, or trowel fill in the area to be repaired, pressing compound firmly into holes or cracks. Wetting the putty knife with water is very helpful to achieve a smooth film.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

3. If area to be patched is deeper than 1/2 inch, apply patch in 1/4-inch layers, maximum depth 1 inch, allowing each application to dry.
4. If used as a "glue," apply at least one layer of concrete patch to both surfaces to be repaired. Push the pieces together and use bracing or weights to support the assembly during cure.
5. Patched areas may be painted with a quality latex paint after 3 to 5 hours or alkyd paint after 48 hours if desired.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Grey
Base Polymer	Latex Emulsion
Weight % Solids	79.6%
Density (lbs per gallon)	11.96
Odor	Mild
Clean Up	Water
Shelf Life	12 months in original unopened container
Coverage	1 QT cover approximately 2 sq. ft. at 1/8 in. 1 GL cover approximately 8 sq. ft. at 1/8 in.
Storage Conditions:	Store between 40°F and 90°F. Keep container tightly sealed when not in use.
Typical Application Properties	
Application Temperature Range	40°F - 90°F
Set Time	3-5 hrs at 1/4" depth
Full Cure	48hrs depending on the temperature and humidity for 1/4" depth



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Clean hands and tools with soap and water. Dry material must be chiseled or scraped away. Keep from freezing. Close container tightly after each use.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS sheet by calling 888-DAP-TIPS or by visiting our website at dap.com.

WARRANTY

Limited Warranty:

If product fails to perform as directed within one year from the date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com