



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Ready-To-Use Concrete Patch

PRODUCT DESCRIPTION

DAP® Ready-To-Use Concrete Patch is a ready to use latex-based compound with fiber reinforcement to increase durability & for a long-lasting repair. Perfect for repairing holes, cracks, breaks & spalls in concrete or masonry surfaces. The product is excellent for tuck pointing masonry and brick work. It may also be used as a “glue” to join broken pieces of concrete or brick. **DO NOT USE AS A SKIM COAT.** The material dries to a concrete-gray color.



PACKAGING	COLOR	UPC
Quart	Gray	7079831084
Gallon	Gray	7079831090

KEY FEATURES & BENEFITS

- Repairs cracks and breaks in concrete and masonry
- Durable and shrink-resistant
- Can be used to spot level

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on concrete.

APPLICATION

1. Stir the patch to a smooth consistency; no thinning is required. With a flexible putty knife, broad knife, or trowel fill in the area to be repaired, pressing compound firmly into holes or cracks. Wetting the putty knife with water is very helpful to achieve a smooth film.
2. If area to be patched is deeper than 1/2 inch, apply patch in 1/4-inch layers, maximum depth 1 inch, allowing each application to dry.
3. If used as a “glue,” apply at least one layer of concrete patch to both surfaces to be repaired. Push the pieces together and use bracing or weights to support the assembly during cure.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Grey
Base Polymer	Latex Emulsion
Weight % Solids	79.6%
Density (lbs per gallon)	11.96
Flash Point	>212°F (>100°C)
Odor	Mild
Clean Up	Water
Shelf Life	12 months in original unopened container
Coverage	1 QT cover approximately 2 sq. ft. at 1/8 in. 1 GL cover approximately 8 sq. ft. at 1/8 in.
Typical Application Properties	
Application Temperature Range	50°F to 90°F
Set Time	3-5 hrs at 1/4" depth
Full Cure	48hrs depending on the temperature and humidity for 1/4" depth



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Clean up excess wet additive with a damp sponge before it skins over. Excess dried additive must be cut or scraped away. Clean skin and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold. Protect from freezing.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS sheet by calling 888-DAP-TIPS or by visiting our website at dap.com.

LIMITED WARRANTY

LIMITED ONE-YEAR WARRANTY: DAP Global Inc. warrants to the original purchaser for a period of one year from the date of purchase that its product will perform to DAP published written product specifications, if used as directed. If the product fails to perform, call 888-DAP-TIPS and return the product and container with your sales receipt for either replacement product or a refund of the sales price, at DAP's sole discretion. Any implied warranties, including the implied warranty of merchantability and fitness for a particular purpose, are expressly limited to the duration of this limited written warranty.

Incidental and consequential damages are expressly disclaimed and DAP's maximum liability is limited to the amount of the original purchase price of the DAP product.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com