



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® CONCRETE & MORTAR REPAIR

PRODUCT DESCRIPTION

DAP® Concrete & Mortar Repair is a ready to use, latex-based compound with fiber reinforcement for a long-lasting repair, perfect for repairing holes, cracks, breaks & spalls in concrete or masonry surfaces. The product is excellent for tuck pointing masonry and brick work. It may also be used as a “glue” to join broken pieces of concrete or brick. **DO NOT USE AS A SKIM COAT.** The material dries to a concrete-gray color.



PACKAGING	COLOR	UPC
Quart	Grey	7079834611

KEY FEATURES & BENEFITS

- Repairs cracks and breaks in concrete and masonry surfaces
- Dries hard for a durable finish
- Resists sinking and shrinking
- Can be used to spot level
- Interior/Exterior use

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on:

- Drywall/plaster
- Wood
- Brick
- Stone



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION

1. Apply concrete patch with a flexible putty knife, broad knife, or trowel. Smooth and feather edge as product cannot be sanded once cured.
2. For repairs greater than 1/2" in thickness (repairs not to exceed 1"), build the compound up in 1/4" layers letting each layer dry for 3 to 5 hours before the next layer is applied. Wetting the putty knife with water is very helpful to achieve a smooth film.
3. For extra adhesion in heavy traffic area, prime area to be patched with DAP Bonding Liquid.
4. Patched areas may be painted with a high-quality latex paint if desired.
5. If material settles in container, mix thoroughly before use. If material is still too stiff, a small amount of water may be added. Mix thoroughly.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency:	Paste
Color	Concrete Gray
Vehicle:	VAE
Odor:	Mild
Solids:	79.6%
Flash Point	>212°F (>100°C)
Application Temperature:	Above 40 °F
Shelf Life:	12 months
Freezing:	Freeze/thaw stable 5 cycles at 0°F
Coverage	1 quart = 2 sq. ft. at 1/8 in. 1 gallon = 8 sq. ft. at 1/8 in.
Set Time**	3-5 hours
Dry Time**	48 hours for 1/4" depth

** Depending on temperature, humidity and depth of repair.

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried material must be removed by scraping or sanding. Be sure container lid is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

LIMITED WARRANTY

LIMITED ONE-YEAR WARRANTY: DAP Global Inc. warrants to the original purchaser for a period of one year from the date of purchase that its product will perform to DAP published written product specifications, if used as directed. If the product fails to perform, call 888-DAP-TIPS and return the product and container with your sales receipt for either replacement product or a refund of the sales price, at DAP's sole discretion. Any implied warranties, including the implied warranty of merchantability and fitness for a particular purpose, are expressly limited to the duration of this limited written warranty. **Incidental and consequential damages are expressly disclaimed and DAP's maximum liability is limited to the amount of the original purchase price of the DAP product.**

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com