



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Weatherproof Patching Compound

PRODUCT DESCRIPTION

DAP® Weatherproof Patching Compound is a ready-to-use formula featuring advanced WeatherMax Technology for a truly weatherproof repair. Once dried, it resists mold, mildew, and algae, and becomes waterproof in just 8 hours, maintaining its integrity even in rain. Unlike traditional patching compounds, it won't swell, crack, or deteriorate—even when exposed to the elements. Ideal for repairing holes, cracks, breaks, and gaps on a wide range of surfaces, including vinyl, wood, fiber cement, concrete, stucco & more. Engineered for exceptional strength and adhesion, this durable solution is built to withstand the demands of exterior repairs. Sandable, paintable, and easy to apply—perfect for both interior and exterior use.



| PACKAGING | COLOR | UPC |
|--------------|-------|------------|
| 16 fl oz tub | White | 7079818741 |
| 32 fl oz tub | White | 7079818787 |

KEY FEATURES & BENEFITS

- Horizontal, vertical & overhead applications of a variety of surfaces
- WeatherMax Technology: weatherproof, mold-, mildew- & algae- resistant when dried
- Waterproof after 8 hours — maintains integrity when exposed to rain
- Resists swelling cracking and deterioration
- Sandable/paintable
- 2-4 hours latex paint ready, depending on temperature, humidity, & depth of fill
- 8-hour rain ready
- Interior/exterior applications



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

USE FOR REPAIRING HOLES, CRACKS, BREAKS, DENTS in:

- Vinyl
- Wood
- Fiber Cement
- Concrete
- Stucco
- Drywall
- Plaster
- Brick
- PVC Trim Board
- Aluminum
- Composite

FOR BEST RESULTS

- Do not apply when temperatures are below 40°F.
- Rain ready in 8 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- Product can be painted with a high-quality latex- based paint.
- Staining is not recommended.
- DO NOT USE AS A SKIM COAT.
- Not for continuous underwater use.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound, and free of all foreign material.

Product Application

1. Apply in temperatures above 40°F. Do not apply when freezing temperatures are forecasted within 24 hours.
2. Apply with a clean putty knife.
3. For a smoother finish, dip putty knife in water and lightly smooth.
4. One application is usually sufficient for small repairs less than 1/8" deep. For repairs deeper than 1/8", apply two or more layers allowing to dry in between applications.
5. May be sanded and/or painted with latex paint in 2 to 4 hours depending on temperature, humidity and depth of fill.
Wet sanding is recommended to avoid generation of dust.
6. Clean tools immediately with water.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

| | |
|--|---|
| Typical Uncured Physical Properties (Mixed) | |
| Appearance/Consistency | Paste |
| Color | White |
| Base Polymer | Acrylic Latex |
| Volatile | Water |
| Flash Point | 212 °F |
| Filler | Inert Filler |
| Odor | Mild |
| Weight/Gallon | 7.3 lbs./gallon |
| Solids | 70% |
| Clean Up | Water |
| Freeze Thaw Stability (ASTM C1183) | Passes at 5 Cycles |
| Shelf Life | 12 months |
| Typical Application Properties | |
| Application Temperature Range | 40°F to 120 °F |
| Dry Time | 2 to 4 hours depending on temperature, humidity & depth of fill. 1" By 1/8 in depth |
| Service Temperature | 0°F to 120°F |
| Typical Dried Performance Properties | |
| Rain Ready Time | 8 hours |
| Mildew Resistance | Once dry is mold & mildew resistant |

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried product must be cut or scraped away. Be sure container is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS sheet by visiting our website at dap.com or calling 888-DAP-TIPS.

07/01/2024



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

LIMITED ONE-YEAR WARRANTY & LIMITED LIFETIME WARRANTY FOR MOLD, MILDEW AND ALGAE: Warranty terms available at dap.com/warranty. For a free written copy, call (888)-DAP-TIPS.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com