



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® 2in1 Wall & Ceiling Spray Texture: Orange Peel Water Based

PRODUCT DESCRIPTION

DAP® 2in1 Wall & Ceiling Spray Texture Orange Peel Water Based is an innovative technology system that allows you to tackle wall, ceiling & hard to reach areas with just one can. DAP's Aim Tech adjustable nozzle can be easily rotated upwards to spray at various angles achieving outstanding coverage. Its ergonomic system provides professional hopper results and excellent spray control. The aerosol can is extremely easy to use, offers a wide fan for even coverage without excessive dripping or clogging. Proven to create a nearly seamless blend with existing textured surfaces by adjusting the texture size to your desired finish. Fast dry time of 30 minutes. Paintable; no priming needed and resists softening and dragging. Interior/Exterior.



| PACKAGING | COLOR | UPC |
|-----------|-------|------------|
| 25 oz can | White | 7079850005 |

KEY FEATURES & BENEFITS

- Ideal for vertical, overhead and hard to reach areas
- Wide coverage with even spray application
- Excellent match to textured surfaces
- 30-minute paint ready time depending on temperature, humidity & amount applied
- Strong and durable cure
- Low odor
- Easy water clean-up

SUGGESTED USES

USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION



Product can be messy. **Protect work area with drop cloths.** Ensure surface is clean, dry, structurally sound and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture. **IMPORTANT:** be sure that the area is well ventilated and proper safety gear is worn.



SHAKE can upside down **vigorously** for more than one minute after hearing mixing marble moving freely in the can. Continue frequently shaking throughout use. Product will not work as intended if this step is surpassed.



UNLOCK tab by bending backwards. THE SAFETY TAB IS DESIGNED TO RE-LOCK, DO NOT BREAK OFF.



ADJUST nozzle upward to desired spray angle, nozzle can rotate up to 60 degrees. BE SURE TO POINT AWAY FROM FACE AND PEOPLE.



TWIST nozzle to desired texture size fine, medium, or heavy.



DISPENSE a quick burst of material on scrap materials to activate before applying to work surface.



SPRAY holding can approximately 12"-18" away from surface using intermittent bursts, sweeping across repair in a quick, continuous motion. **IMPORTANT:** keep frequently shaking throughout use & keep tip/nozzle clean while spraying by wiping with damp cloth. For superior blending, feather repair texture into surrounding area. Add coverage as needed to match existing texture density. If not satisfied, scrape off & reapply.



PAINT: Allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior/moisture exposed applications, apply a waterproof coating prior to moisture exposure.



CLEAN-UP: Wet texture can be cleaned up with water. Dry texture must be cut, scraped or sanded away. Place nozzle in the upright position, invert can by pointing straight down. Spray onto a disposable surface until no texture sprays outs. Be sure to remove any texture build up from tip/nozzle to prevent material drying on tip/nozzle. **STORE:** adjust spray angle to starting position and re-lock using tab. Store in cool, dry conditions.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- **IMPORTANT: Shake vigorously** before attempting to spray, and frequently during application.
NOTE: If an attempt to spray the product has been made prior to properly shaking and activating the can, reduced spray performance may occur. This condition is potentially not correctable.
- Dispense a quick burst on scrap material to activate
- Apply in temperatures between 65°F to 80°F
- Spray using intermittent bursts
- Practice applying on scrap material before use
- Store away from direct heat in temperatures ranging from 40°F to 90°F

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

| TYPICAL PHYSICAL & CHEMICAL PROPERTIES | |
|---|--|
| Typical Uncured Physical Properties | |
| Appearance/Consistency | White textured material |
| Base Polymer | Acrylic Latex |
| Weight % Solids | 54.9% |
| Density (lbs per gallon) | 11.3 |
| Odor | Low odor |
| Clean Up | Water |
| Shelf Life | 12 months |
| Coverage | Fine: up to 130 sq. ft. Medium: up to 90 sq. ft. Heavy: up to 70 sq. ft. |
| Typical Application Properties | |
| Application Temperature Range | Best between 65°F - 80°F |
| Typical Cured Performance Properties | |
| Service Temperature Range | 40° F - 90° F |

CLEAN UP & STORAGE

Clean-up wet texture with water. Dry texture must be cut, scrape or sanded away. Store in cool, dry conditions.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

LIMITED WARRANTY

LIMITED ONE-YEAR WARRANTY: Warranty terms available at dap.com/warranty. For a free written copy, call (888)-DAP-TIPS.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com