



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® 2in1 Wall & Ceiling Spray Texture: Knockdown Water Based

PRODUCT DESCRIPTION

DAP® 2in1 Wall & Ceiling Knockdown Water Based is an innovative technology system that allows you to tackle wall, ceiling & hard to reach areas with just one can. DAP's Aim Tech nozzle can be easily rotated upwards to spray at various angles achieving outstanding coverage. Its ergonomic system provides professional hopper results and ultimate spray control. The formula is clog-resistant, the aerosol can is extremely easy to use and offers a wide fan for even coverage. Create a seamless blend with existing textured surfaces by adjusting the texture size to your desired finish. Fast dry time of 30 minutes. Excellent paintability; no priming needed and resists softening and or dragging. Interior/Exterior.



PACKAGING	COLOR	UPC
25 oz can	White	7079850010

KEY FEATURES & BENEFITS

- Ideal for vertical, overhead and hard to reach areas
- Wide coverage with even spray application
- Excellent match to textured surfaces
- 30 minute paint ready time, depending on temperature, humidity and amount applied
- Strong and durable cure
- Low odor
- Easy water clean-up
- Interior/exterior

SUGGESTED USES

USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION



Product can be messy. **Protect work area with drop cloths.** Ensure surface is clean, dry, structurally sound and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture. **IMPORTANT:** be sure that the area is well ventilated and proper safety gear is worn.



SHAKE can upside down **vigorously** for more than one minute after hearing mixing marble moving freely in the can. Continue frequently shaking throughout use. Product will not work as intended if this step is surpassed.



UNLOCK tab by bending backwards. THE SAFETY TAB IS DESIGNED TO RE-LOCK, DO NOT BREAK OFF.



ADJUST nozzle upward to desired spray angle, nozzle can rotate up to 60 degrees. **BE SURE TO POINT AWAY FROM FACE AND PEOPLE.**




TWIST nozzle to desired texture size fine, medium, or heavy.



DISPENSE a quick burst of material on scrap materials to activate before applying to work surface.



SPRAY holding can approximately 12"-18" away from surface using intermittent bursts, sweeping across repair in a quick, continuous motion. **IMPORTANT:** keep frequently shaking throughout use & keep tip/nozzle clean while spraying by wiping with damp cloth. For superior blending, feather repair texture into surrounding area. Add coverage as needed to match existing texture density. If not satisfied, scrape off & reapply.



KNOCKDOWN: Allow spray texture to dry: immediately for fine, 30 secs to 1 minute for medium and 1-2 minutes for heavy. Hold putty knife parallel to the wall or ceiling and lightly flatten knockdown to desired texture. **IMPORTANT** be sure to dip putty knife into water in between each knockdown. Dry time is dependent on temperature, texture size and thickness of material sprayed.



PAINT: Allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior/moisture exposed applications, apply a waterproof coating prior to moisture exposure.



CLEAN-UP: Wet texture can be cleaned up with water. Dry texture must be cut, scraped or sanded away. Place nozzle in the upright position, invert can by pointing straight down. Spray onto a disposable surface until no texture sprays outs. Be sure to remove any texture build up from tip/nozzle to prevent material drying on tip/nozzle. **STORE:** adjust spray angle to starting position and re-lock using tab. Store in cool, dry conditions.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- **IMPORTANT: Shake vigorously** before attempting to spray, and frequently during application.
NOTE: If an attempt to spray the product has been made prior to properly shaking and activating the can, reduced spray performance may occur. This condition is potentially not correctable.
- Protect work area with drop cloths
- Dispense a quick burst on scrap material to activate can or contents
- Apply in temperatures between: 65°F to 80°F
- Spray using intermittent bursts
- Practice applying on scrap material before use
- Dip putty knife in water before each knockdown stroke
- Store between 40°F to 90°F

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

TYPICAL PHYSICAL & CHEMICAL PROPERTIES	
Typical Uncured Physical Properties	
Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	55.3%
Density (lbs per gallon)	11.55
Odor	Low odor
Clean Up	Water
Shelf Life	12 months
Coverage	Fine: up to 130 sq. ft. Medium: up to 90 sq. ft. Heavy: up to 70 sq. ft.
Typical Application Properties	
Application Temperature Range	Best between 65°F - 80°F
Typical Cured Performance Properties	
Service Temperature Range	40°F - 90°F

CLEAN UP & STORAGE

Clean-up wet texture with water. Dry texture must be cut, scraped or sanded away. Store in cool, dry conditions.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

LIMITED ONE-YEAR WARRANTY: Warranty terms available at dap.com/warranty. For a free written copy, call (888)-DAP-TIPS.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com