



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® Wall Spray Texture: Orange Peel Oil Based

### PRODUCT DESCRIPTION



**DAP® Wall Spray Texture Orange Peel Oil Based** is an easy to use aerosol that provides excellent texture match. Its white, sag-resistant formula has strong wall adhesion, is paintable, and does not require priming. The grip trigger offers full hand control for an ergonomic spray. Fast dry time of 5 minutes depending on temperature, humidity & amount applied. Interior/Exterior.

PACKAGING	COLOR	UPC
20 oz can	White	7079850016

### KEY FEATURES & BENEFITS

- Adjustable for excellent texture match
- 5-minute paint ready time depending on temperature, humidity & amount applied
- Strong adhesion – sag-resistant formula
- Texture and prime in one step
- Control grip trigger
- Stronger odor
- Mineral spirits clean-up

### SUGGESTED USES

#### USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## FOR BEST RESULTS

**IMPORTANT:** Shake well before and frequently during spraying

- Cover surrounding areas to prevent over spray
- Apply in temperatures above 40°F
- Be sure area is well ventilated during application
- Dispense a quick burst on scrap material to activate pressure
- Practice applying on scrap material before applying
- Spray using intermittent bursts
- Store away from direct heat in temperatures ranging from 40°F to 90°F
- While this formula does not require priming prior to paint application, priming may still be desired depending on your project/application requirements

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.

### Product Application

1. **SHAKE** can upside down vigorously for more than a minute after hearing mixing marble moving freely in the can.
2. **TEAR OFF** top safety tab by pulling tab from front to back of top of nozzle. This safety tab is not reusable, and it is meant to be broken off.  
**IMPORTANT:** Dispense a quick burst of material on scrap materials to activate before applying to surface.
3. **ADJUST** texture: for medium to heavy texture spray without straw insert. For heavier texture, overlap texture sprays. For finer texture, firmly insert straw into nozzle tip.  
**IMPORTANT:** Practice using scrap material before applying onto the wall.
4. **SPRAY** holding can approximately 12 to 18 inches away from surface using intermittent bursts. For optimal blending, use different stroke motions like up and down, or left to right. Apply texture in overlapping passes to avoid gaps or uneven spots. If not satisfied, scrape-off and reapply. **IMPORTANT:** Be sure that the area is well ventilated and proper safety gear is worn.
5. **PAINT:** Allow texture to dry for 5 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow the paint manufacturer's instructions for best results. For exterior applications, use exterior grade paint.
6. **CLEAN-UP** straw, nozzle, tools and area with towel and mineral spirit, Acetone or IPA. Be sure to remove any texture build up from tip/nozzle to prevent material drying on tip. Invert can point the top straight down. Spray a quick burst onto a disposable surface until texture is cleared from tip.
7. **STORE** at room temperature, avoid extreme cold or heat.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	White textured material
Base Polymer	Acrylic resin
Weight % Solids	64.0%
Density (lbs per gallon)	10.9
Odor	Strong odor
Clean Up	Mineral spirits, Acetone or IPA
Shelf Life	12 months
Coverage	Fine: up to 130 sq. ft. Medium: up to 90 sq. ft. Heavy: up to 70 sq. ft.
Typical Application Properties	
Application Temperature Range	Best between 65°F-80°F

## CLEAN UP & STORAGE

Uncured material can be cleaned up with mineral spirits, Acetone or IPA. Excess cured material can be scraped off or sanded down. Store away from direct heat in temperatures ranging from 40°F to 90°F

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.

## LIMITED WARRANTY

**Limited Warranty:** If product fails to perform as directed within one year from the date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland

21224 **Usage Information:** Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on “Ask the

Expert” **Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**