



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Ceiling Spray Texture: Popcorn Water Based

PRODUCT DESCRIPTION

DAP® Ceiling Spray Texture Popcorn Water Based is an easy-to-use aerosol that provides excellent texture match. Its white, sag-resistant formula has strong ceiling adhesion and does not require painting or priming. Fast dry time of 30 minutes, depending on temperature, humidity & amount applied. Interior/Exterior.



PACKAGING	COLOR	UPC
16 oz can	White	7079850035

KEY FEATURES & BENEFITS

- Ideal for ceiling applications
- Excellent match to textured surfaces
- 30-minute paint ready time depending on temperature, humidity & amount applied
- Sag-resistant formula
- No priming required
- Low odor
- Easy water clean-up
- Interior/ Exterior

SUGGESTED USES

USE FOR REPAIRING TEXTURED SURFACES

- Drywall
- Stucco
- Plaster



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION



Product can be messy. **Protect work area with drop cloths.** Ensure surface is clean, dry, structurally sound and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture. **IMPORTANT:** be sure that the area is well ventilated and proper safety gear is worn.



SHAKE can upside down **vigorously** for more than one minute after hearing mixing marble moving freely in the can. Continue frequently shaking throughout use. Product will not work as intended if this step is surpassed.



DISPENSE a quick burst of material on scrap materials to activate before applying to work surface.



REMOVE over-cap. **INSERT** straw attachment into tip of actuator.



SPRAY by placing finger on designated indentation at the base of the actuator, holding can approximately 12 inches away from ceiling. **DO NOT SPRAY** directly above you. Spray using intermittent bursts. For optimal blending, use different stroke motions or a circular pattern. Apply texture in overlapping passes to avoid gaps or uneven spots. If not satisfied, scrape-off and reapply. **IMPORTANT:** keep continue frequently shaking throughout use and be sure that the area is well ventilated and proper safety gear is worn.



PAINT: Allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior/moisture exposed applications, apply a waterproof coating prior to moisture exposure.



CLEAN-UP straw, nozzle, tools, and area with towel and warm water. Invert can point the top straight down. Spray a quick burst onto a disposable surface until texture is cleared from tip. Remove any texture build-up from the nozzle. Store at room temperature, avoid extreme cold or heat. .



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- **IMPORTANT: Shake vigorously** before attempting to spray, and frequently during application.
NOTE: If an attempt to spray the product has been made prior to properly shaking and activating the can, reduced spray performance may occur. This condition is potentially not correctable.
- Cover surrounding areas to protect from over spray
- Dispense a quick burst on scrap material to activate
- Apply in temperatures between 60°F and 85°F
- Practice applying on scrap material before applying
- Spray using intermittent bursts
- Store away from direct heat in temperatures ranging from 40°F to 90°F
- While this formula does not require priming prior to paint application, priming may still be desired depending on your project/application requirements.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	47.7%
Density (lbs per gallon)	10.74
Odor	Low Odor
Clean Up	Water
Shelf Life	12 months
Calculated Coverage	Up to 9 sq. ft. depending on thickness of application
Typical Application Properties	
Application Temperature Range	60°F - 85°F

CLEAN UP & STORAGE

Clean up excess wet spray texture with warm water and soap. Excess dried spray texture must be cut or scraped away. Clean skin with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

LIMITED WARRANTY

LIMITED ONE-YEAR WARRANTY: Warranty terms available at dap.com/warranty. For a free written copy, call (888)-DAP-TIPS.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com